

heavy duty cartridges



WDGD-5005-20

heavy-duty spun polypropylene

Manufactured from pure 100% polypropylene
Excellent bacteria and chemical resistance
Spun fibers provide a variable density from the outer surface to inner core
Available in two different lengths and micron ratings



Tested and Certified by NSF International.



W50PEHD

pleated polyester

Polyester media is extremely durable and reusable*
Excellent for well water applications
Reduces particles as small as 30 and 50 micron in size by mechanical means

**Reuse not recommended for potable water applications*



W20CLHD

W20CLHD20

pleated cellulose

Economical priced
Pleated design maximizes dirt-holding capacity
Reduces particles as small as 5 & 20 micron in size by mechanical means
Designed for municipal/chlorinated water (not recommended for well water applications)
Good for general purpose filtration



WRC25HD

WRC25HD20

radial flow carbon

Ideal for POE (whole house) and other high flow rate applications
Reduces particles as small as 25 micron in size by mechanical means
Effectively reduces bad taste and odor and chlorine taste & odor from water
Recommended for whole house taste and odor filtration



The WRC25HD is tested and Certified by NSF International.

The WRC25HD20 is tested and Certified by NSF International for material requirements only.



WGCHD

granular activated carbon (GAC)

Effective taste, odor, and chlorine taste & odor reduction
Cartridge design ensures that water passes through the entire length of the carbon bed maximizing contact time
Reduces particles as small as 20 micron in size by mechanical means
Ideal for high volume applications with flow rates less than 2 gpm
(Not recommended for whole house applications)



W.5CBHD

granular activated carbon (GAC)

Excellent for bad taste, odor, and chlorine taste & odor reduction

Certain states require registration or certification for health-related reduction claims.

		housings									housings											
Filter Cartridge		Micron Rating †	1" Heavy Duty	W10-PR 10"	W10-BC 10"	W2010-PR 20"	1-1/2" Heavy Duty	W15-PR 10"	W15-BL 10"	W2015-PR 20"	Filter Cartridge		Micron Rating †	1" Heavy Duty	W10-PR 10"	W10-BC 10"	W2010-PR 20"	1-1/2" Heavy Duty	W15-PR 10"	W15-BL 10"	W2015-PR 20"	
cartridges	Sediment		Flow Rate* (gpm)									Drinking Water		Flow Rate* (gpm)								
	WDGD-5005	5		10	10			10	10			WGCHD			2	2			2	2		
	W5CPHD	5		20	20	20*		20	20	20*		Whole House Taste & Odor		Flow Rate* (gpm)								
	W20CLHD	20		20	20	20*		20	20	20*				Flow Rate* (gpm)								
	WDGD-7525	25		10	10			10	10			W.5CBHD	0.5		4	4			4	4		
	W30PEHD	30		25	25	25*		25	25	25*		WRC25HD	25		3	3			3	3		
	W50PEHD	50		25	25	25*		25	25	25*		WRC25HD20	25				8					8
	W20CLHD20	20				25				25												

*With two cartridges and a cartridge coupler

**Flow rates are calculated for cartridges according to the housing in which they are being used

† Micron ratings are nominal

EPA Est. 082989-CHN-001

EPA Est. 090375-MEX-001

Spun Polypropylene Dual Gradient Depth					
Model	Medium	Micron Rating (nominal)	Max. Flow Rate (gpm)	Diameter	Length
WDGD-5005	Polypropylene	50/5	10	4-1/2"	9-7/8"
WDGD-7525	Polypropylene	75/25	10	4-1/2"	9-7/8"
WDGD-5005-20	Polypropylene	50/5	20	4-1/2"	20"
WDGD-7525-20	Polypropylene	75/25	20	4-1/2"	20"
Pleated Polyester					
W30PEHD	Polyester	30	25	4-1/2"	9-3/4"
W50PEHD	Polyester	50	25	4-1/2"	9-3/4"
Pleated Cellulose					
W20CLHD	Cellulose	20	20	4-1/2"	9-3/4"
W20CLHD20	Cellulose	20	25	4-1/2"	20"

Radial Flow Carbon						
Model	Part	Medium	Chlorine Taste & Odor Reduction @ Flow Rate	Max. Flow Rate (gpm)	Diameter	Length
WRC25HD	155141-51	Granular Activated Carbon	5,000# Gallons @ 3 GPM	3	4-1/2"	9-3/4"
WRC25HD20	155247-51	Granular Activated Carbon	10,000 Gallons @ 4 GPM	8	4-1/2"	20"

Granular Activated Carbon (GAC)						
Model	Part	Medium	Chlorine Taste & Odor Reduction @ Flow Rate	Max. Flow Rate (gpm)	Diameter	Length
WGCHD	155153-51	Granular Activated Carbon	>12,500# Gallons @ 2 GPM	2	4-1/2"	9-3/4"

Carbon Block Cartridges								
Model	Part	Medium	Reduces	Micron Rating (nominal)	Chlorine Taste & Odor Reduction @ Flow Rate	Max. Flow Rate (gpm)	Diameter	Length
W.5CBHD	155170-51	Acid-Washed Bituminous Carbon	Chlorine Taste & Odor	0.5	5,000 Gallons @ 4 GPM	4	4-5/8"	9-3/4"

#NSF Tested Capacity



WATER QUALITY SYSTEMS

5730 NORTH GLEN PARK ROAD, MILWAUKEE, WI 53209
P: 262.238.4400 | AMERICANPLUMBER.COM | CUSTOMER CARE: 800.279.9404 | tech-support@pentair.com

§For a detailed list of where Pentair trademarks are registered, please visit waterpurification.pentair.com/brands. Pentair trademarks and logos are owned by Pentair plc or its affiliates. Third party registered and unregistered trademarks and logos are the property of their respective owners. Because we are continuously improving our products and services, Pentair reserves the right to change specifications without prior notice. Pentair is an equal opportunity employer.